



A product of Mill Services, Inc., Cobleskill, NY

***Thank you for purchasing EASTERN
finger joint boards manufactured
in New York from locally harvested
Eastern White Pine!***

***This product is ideal for applications
requiring durable, knot-free trim boards
for above-ground use.***

How to Store, Install and Finish your EASTERN Boards

For best results and to meet the conditions of your warranty, please follow these instructions for the care and installation of your EASTERN finger joint boards.

Storage

All lumber should be stored off the ground (a minimum of 12") and out of the weather. Make sure to cover the lumber securely, but loose enough to allow air flow. Store lumber away from direct sunlight and extreme heat. Do not let lumber get wet or dirty. When storing lumber near the ground, place a plastic cover over soil to minimize moisture absorption.

Installation

All EASTERN primed lumber has been sealed on all faces, edges and ends for maximum protection and complete coverage. When cutting the lumber, be sure to seal all cuts with primer to ensure protection and extended preservation of the product.

Finishing

Top coat with any premium brand 100% acrylic paint as soon as possible. For best results, we recommend top coating within six months after installation of the product. Be sure the EASTERN boards are clean and dry before top coating to ensure the best possible adhesion.

The EASTERN 15-Year Warranty

Please refer to the instructions on the reverse side for storing, installing and finishing your EASTERN boards. The following warranty applies if all conditions have been met:

- ▶ Eastern Forest Products hereby warrants all of its primed products against failure for as long as you own your home for up to 15 years.
- ▶ Should any EASTERN products prove to be defective within the warranty period, Eastern Forest Products reserves the right to inspect said failure and decide to replace or repair defective lumber, at the company's sole discretion. No related damages are recoverable.

Eastern Forest Products' warranties apply only when the lumber is coated in a manner as to completely cover the substrate. The field-applied top coat finish is to be two coats of any premium 100% acrylic trim paint and will be characterized by complete film uniformity and the absence of voids, thin spots, pin holes or any coating defect which will allow the infiltration of water once the trim has been installed. All cut ends of lumber must be sealed with a premium 100% acrylic primer prior to installation. The warranty does not apply to construction defects or breaching of the coating envelope by the building contractor or his or her subcontractors. The contractor is responsible for proper storage of the lumber on the job site as well as approval of the primed product, prior to installation.

For more information:

Eastern Forest Products

(800) 578-2119

www.easternfp.com/easternbrand.html

